

Technical Data	GW1000-NS	GW1500-NS	GW2000-NS	GW2500-NS	GW3000-NS
<b>DC Input Data</b>					
Max. allowed PV Power [W]	1300	1950	2600	3250	3900
Nominal DC Power [W]	1200	1800	2300	2700	3200
Max. DC voltage [V]	500	500	500	500	500
MPPT voltage range [V]	80~450	80~450	80~450	80~450	80~450
Starting voltage [V]	80	80	80	80	80
Max. DC current [A]	10	10	10	18	18
No. of DC connectors	1	1	1	1	1
No. of MPPTs	1	1	1	1	1
DC connector	MC4/ Phoenix/ Amphenol			MC4/ Phoenix/ Amphenol	
<b>AC Output Data</b>					
Nominal AC power [W]	1000	1500	2000	2500	3000
Max. AC power [W]	1000	1500	2000	2500	3000
Max. AC current [A]	5	7.5	10	12.5	13.5
Nominal AC output	50/60Hz; 230Vac			50/60Hz; 230Vac	
AC output range	45~55Hz/55~65Hz; 180~270Vac			45~55Hz/55~65Hz; 180~270Vac	
THDi	<3%			<3%	
Power factor	0.8 leading~0.8 lagging			0.8 leading~0.8 lagging	
Grid connection	Single phase	Single phase	Single phase	Single phase	Single phase
<b>Efficiency</b>					
Max. efficiency	96.5%	97.0%	97.0%	97.5%	97.5%
Euro efficiency	>96.0%	>96.0%	>96.0%	>97.0%	>97.0%
MPPT adaptation efficiency	99.9%	99.9%	99.9%	99.9%	99.9%
<b>Protection</b>					
Residual current monitoring unit	Integrated			Integrated	
Anti-islanding protection	Integrated			Integrated	
DC switch	Integrated (optional)			Integrated (optional)	
AC over current protection	Integrated			Integrated	
Insulation monitoring	Integrated			Integrated	
<b>Certifications &amp; Standards</b>					
Grid regulation	G83/2, VDE0126-1-1, AS4777.2&.3, EN50438, ERDF-NOI-RES_13E;			G83/2, VDE0126-1-1, AS4777.2&.3, EN50438, ERDF-NOI-RES_13E;	
Safety	According to IEC62109-1&-2, AS3100			According to IEC62109-1&-2, AS3100	
EMC	EN 61000-6-1, EN 61000-6-2, EN 61000-6-3, EN 61000-6-4, EN 61000-3-2, EN 61000-3-3			EN 61000-6-1, EN 61000-6-2, EN 61000-6-3, EN 61000-6-4, EN 61000-3-2, EN 61000-3-3	
<b>General Data</b>					
Dimensions (WxHxD) [mm]	344*274.5*128			344*274.5*128	
Weight [kg]	7.5			8.5	
Mounting	Wall bracket			Wall bracket	
Ambient temperature range	-25~60°C (> 45°C derating)			-25~60°C (> 45°C derating)	
Relative humidity	0~95%			0~95%	
Max. operating altitude	4000m(> 3000m derating)			4000m(> 3000m derating)	
Protection degree	IP65			IP65	
Topology	Transformerless			Transformerless	
Night power consumption [W]	<1			<1	
Cooling	Natural convection			Natural convection	
Noise emission [dB]	<25			<25	
Display	LCD			LCD	
Communication	Wi-Fi; RS485 or Ethernet			Wi-Fi; RS485 or Ethernet	
Standard warranty [years]	5/10/15/20/25 (optional)			5/10/15/20/25 (optional)	

Color Options